



Piston pneumatic pump for medium pressure professional air assisted-airless paint spraying, suitable for the wood and metal sectors.

CODE	DESCRIPTION
TKP303B	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Suction system

APOLLO 303		
Ratio		30:1
Pump capacity per cycle	cm³	40
Stroke	mm	60
Max. Delivery free flow	ltr/min	4
Number of strokes per liter	Bar (PSI)	25
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	14
Air consumption	ltr/min	250 - 400
Packing type		Fixed
Material inlet fitting size		M 3/4"
Material outlet fitting size		M 1/4"
Packing material		PTFE - PE

APPLICATION

Suitable for low and medium viscosity varnish, lacquers, enamels and primer.
All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
TT1001	MACH 3 AIR-ASSISTED AIRLESS SPRAY GUN
6616750	HP TWIN HOSE 3/16" + 1/4" MT 7,5 1/4" CONN.
FM61000	WHITE 6L GRAVITY TANK
FM610061	"U" OBLIQUE ADAPTER M36x2mm X F3/4"

ACCESSORIES KIT	
TRK303P	REPAIR KIT GASKET PUMP
690349I	S.S. STEEL SUCTION SYSTEM Ø13 F 3/4" 90° M15x1 450mm
690349AK	FM60005 SUCTION HOUSING KIT F15x1mm
	RAP3040R7 RETURN HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP303F	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Gravity tank with adapter



CODE	DESCRIPTION
TKP303E	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Suction system



CODE	DESCRIPTION
TKP303A	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter



CODE	DESCRIPTION
TKP303C	APOLLO 303 Pneumatic air-assisted airless pump on bracket - Pressure regulator - Stainless steel inline filter



CODE	DESCRIPTION
TKP303G	APOLLO 303 Pneumatic air-assisted airless pump C/ Stainless steel inline filter



APOLLO
303R

Inverted piston pneumatic pump for medium pressure air assisted-airless paint spraying, suitable for the wood and metal sectors.

CODE	DESCRIPTION
TKP303H	APOLLO 303R Air-assisted airless inverted pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose 7,5m - Mach3 spray gun - Gravity tank

		APOLLO 303R
Ratio		30:1
Pump capacity per cycle	cm³	40
Stroke	mm	60
Max. Delivery free flow	ltr/min	4
Number of strokes per liter	Bar (PSI)	25
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	14
Air consumption	ltr/min	250 - 400
Packing type		Fixed
Material inlet fitting size		M 3/4"
Material outlet fitting size		M 1/4"
Packing material		PTFE - PE

APPLICATION

Suitable for low and medium viscosity varnish, lacquers, enamels and primer.
All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
TT1001	MACH 3 AIR-ASSISTED AIRLESS SPRAY GUN
6616750	HP TWIN HOSE 3/16" +1/4" MT 7,5 1/4" CONN.
FM61000	WHITE 6L GRAVITY TANK
FM610061	"U" OBLIQUE ADAPTER M36x2mm X F3/4"

ACCESSORIES KIT	
TRK303P	REPAIR KIT GASKET PUMP
690349I	S. STEEL SUCTION SYSTEM Ø13 F3/4" 90° M15x1 450mm
690349AK	FM60005 SUCTION HOUSING KIT F15x1mm
RAP3040	R7 RETURN HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP303D	APOLLO 303R Air-assisted airless inverted pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank

CODE	DESCRIPTION
TKP303I	APOLLO 303R Air-assisted airless inverted pump on bracket - Pressure regulator - Stainless steel inline filter - Gravity tank

AIR-ASSISTED
AIRLESS



APOLLO
30

Piston pneumatic air-assisted airless pump for medium pressure professional paint spraying, suitable for the wood and metal sectors. Available in the airless model.

CODE	DESCRIPTION
TKB30G	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Complete suction system

APOLLO 30		
Ratio		30:1
Pump capacity per cycle	cm ³	37
Stroke	mm	100
Max. Delivery free flow	ltr/min	7
Number of strokes per liter	Bar (PSI)	27
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	27
Air consumption	ltr/min	250 - 750
Packing type		Fixed
Material inlet fitting size		M 3/4"
Material outlet fitting size		M 1/4"
Packing material		PTFE - PE

APPLICATION

Suitable for low and medium viscosity varnish, lacquers, enamels and primers. All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
TT1001	MACH 3 AIR-ASSISTED AIRLESS SPRAY GUN
6616750	HP TWIN HOSE 3/16" +1/4" MT 7,5 1/4" CONN.
FM61000	WHITE 6L GRAVITY TANK
FM610061	"U" OBLIQUE ADAPTER M36x2mm XF36x2mm

ACCESSORIES KIT	
TRK3001P	REPAIR KIT GASKET PUMP
69034912I	S.S. STEEL SUCTION SYSTEM Ø19 F3/4" 90° M1/2" 750mm
69034912AK	FM60004 SUCTION HOUSING KIT F1/2"
RAP3040	R7 RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKB30H	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Gravity tank with adapter



COD	DESCRIZIONE
TKB30E	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKB30F	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter



CODE	DESCRIPTION
TKB30I	APOLLO 30 Piston pneumatic air-assisted airless pump on bracket - Pressure regulator - Stainless steel inline filter



CODE	DESCRIPTION
TKB30C	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Stainless steel inline filter

AIRLESS



APOLLO 30

Piston pneumatic airless pump for medium pressure professional paint spraying, suitable for the wood and metal sectors.
Available in the air-assisted airless model.

CODE	DESCRIPTION
TKB30L	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5 m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

		APOLLO 30
Ratio		30:1
Pump capacity per cycle	cm³	37
Stroke	mm	100
Max. Delivery free flow	ltr/min	7
Number of strokes per liter	Bar (PSI)	27
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	27
Air consumption	ltr/min	250 - 750
Packing type		Fixed
Material inlet fitting size		M 3/4"
Material outlet fitting size		M 1/4"
Packing material		PTFE - PE

APPLICATION

Suitable for low and medium viscosity varnish, lacquers, enamels and primers.
All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
RST11	HP RST1 SPRAY GUN 1/4" CONN.
614754	HP HOSE 1/4" MT 7,5 1/4" CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
FM610061	"U" OBLIQUE ADAPTER M36x2mm X F3/4"
TRK3001P	REPAIR KIT GASKET PUMP
69034912I	S.S. STEEL SUCTION SYSTEM Ø19 F3/4" 90° M1/2" 750mm
FM60004	SUCTION HOUSING KIT F1/2"
RAP3040R7	RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKB30M	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5 m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank with adapter



CODE	DESCRIPTION
TKB30A	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKB30D	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter



CODE	DESCRIPTION
TKB30B	APOLLO 30 Piston pneumatic airless pump on bracket - Pressure regulation control plate - Stainless steel inline filter



CODE	DESCRIPTION
TKB30C	APOLLO 30 Piston pneumatic airless pump C/ Stainless steel inline filter

AIR-ASSISTED
AIRLESS



APOLLO
40

Piston pneumatic air-assisted airless pump for medium pressure professional paint spraying, suitable for the wood and metal sectors. Available in the airless model.

CODE	DESCRIPTION
TKP401AB	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5m - Mach3 spray gun - Complete suction system

		APOLLO 40
Ratio		40:1
Pump capacity per cycle	cm³	50
Stroke	mm	80
Max. Delivery free flow	ltr/min	9
Number of strokes per liter	Bar (PSI)	20
Max. Working outlet pressure	Bar (PSI)	320 (4640)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	32
Air consumption	ltr/min	250 - 1000
Packing type		Mobile
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 1/4"
Packing material		PTFE-PE-LEATHER

APPLICATION

Suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
TT1001	HP MACH 3 SPRAY GUN
6616750	HP TWIN HOSE 3/16" +1/4" MT 7,5 1/4 CONN.
FM61000	WHITE 6L GRAVITY TANK
FM610062	"U" OBLIQUE ADAPTER M36x2mm XF36x2mm

ACCESSORIES KIT	
TRK4010P	REPAIR KIT GASKET PUMP
69362912AK	69362912IS.STEEL SUCTION SYSTEM Ø19 F36x2 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	RAP3040 R7 RETURNED HOSE Ø1/4" MT 1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP401AC	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5m - Mach3 spray gun - Gravity tank with adapter



CODE	DESCRIPTION
TKP401AA	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKP401AD	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter



CODE	DESCRIPTION
TKP401AE	APOLLO 40 Piston pneumatic air-assisted airless pump on bracket - Pressure regulators - Stainless steel inline filter



CODE	DESCRIPTION
TKP401F	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Stainless steel inline filter

AIRLESS



APOLLO 40

Piston pneumatic airless pump for medium pressure professional paint spraying, suitable for the wood and metal sectors.
Available in the air-assisted airless model.

CODE	DESCRIPTION
TKP401B	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

APOLLO 40		
Ratio		40:1
Pump capacity per cycle	cm³	50
Stroke	mm	80
Max. Delivery free flow	ltr/min	9
Number of strokes per liter	Bar (PSI)	20
Max. Working outlet pressure	Bar (PSI)	320 (4640)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	32
Air consumption	ltr/min	250 - 1000
Packing type		Mobile
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 1/4"
Packing material		PTFE-PE-LEATHER

APPLICATION

Suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
RST21	HP RST2 SPRAY GUN 1/4" CONN.
614754	HP HOSE 1/4" MT 7,5 1/4" CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
FM610062	"U" OBLIQUE ADAPTER M36x2mm XF36x2mm
TRK4010P	REPAIR KIT GASKET PUMP
69034912I	S.S. STEEL SUCTION SYSTEM Ø19 F3/4" 90° M1/2" 750mm
69362912AK	FM60004 SUCTION HOUSING KIT F1/2"
RAP3040	R7 RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP401D	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank with adapter



CODE	DESCRIPTION
TKP401A	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKP401E	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter



CODE	DESCRIPTION
TKP401C	APOLLO 40 Piston pneumatic airless pump on bracket with pressure regulators - Stainless steel inline filter



CODE	DESCRIPTION
TKP401F	APOLLO 40 Piston pneumatic airless pump C/ Stainless steel inline filter



APOLLO
40 Mix

Two component pneumatic airless piston pump for high pressure paint spraying, suitable for treating paint and anti-corrosion with high viscosity products.

CODE	DESCRIPTION
TK97995	APOLLO 40 Mix Two component pneumatic airless pump C/ Trolley - Pressure regulator - 2 Inline filters - 2 Complete suction systems - Static mixer APOLLO 303 Piston pneumatic pump flushing pump - Pressure regulator - Complete suction system

		APOLLO 40 MIX
Ratio		40:1
Mixing ratio	cm ³	1:1
Pump capacity per cycle	cm ³	73
Stroke	mm	80
Max. Delivery free flow	ltr/min	9
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	45
Air consumption	ltr/min	250 - 400
Packing type		Fixed
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm
Packing material		PTFE-PE

APPLICATION

Suitable for treating paint and anti-corrosion with high viscosity products. It can be used in the naval, civil and industrial construction sectors and heavy carpentry, with bicomponent products, paint, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins.
All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
RST21	HP RST2 SPRAY GUN 1/4" CONN.
614754	HP HOSE 1/4" MT 7,5 1/4" CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6 L GRAVITY TANK

ACCESSORIES KIT	
FM610062	"U" OBLIQUE ADAPTER M36x2mm X F36x2mm
TRK307P	REPAIR KIT GASKET PUMP
69362912AK	69362912I S. STEEL SUCTION HOSE Ø19 F3/4" 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	RAP3040R7 RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP40MIX	APOLLO 40 Mix Two component pneumatic airless pump C/ Trolley - Pressure regulator control plate - 2 Inline filters - 2 Complete suction systems - Static mixer



CODE	DESCRIPTION
TKP40MIXB	APOLLO 40 Mix Two component pneumatic airless pump C/ Trolley - Pressure regulator control plate - 2 Inline filters - 2 Gravity tanks with adapter - Static mixer



APOLLO 48

Pneumatic airless piston pump for high pressure professional paint spraying, suitable for treating paint and anti-corrosion with high viscosity products.

CODE	DESCRIPTION
TKP4825C	APOLLO 48 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

		APOLLO 48
Ratio		48:1
Pump capacity per cycle	cm³	143
Stroke	mm	100
Max. Delivery free flow	ltr/min	18
Number of strokes per liter	Bar (PSI)	7
Max. Working outlet pressure	Bar (PSI)	348 (5569)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	64
Air consumption	ltr/min	600 -2650
Packing type		Fixed
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm
Packing material		PTFE-PE-LEATHER

APPLICATION

Suitable for treating paint and anti-corrosion with high viscosity products. It can be used in the naval, civil and industrial construction sectors and heavy carpentry, with bicomponent products, paint, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins. All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
RST22	HP RST2 SPRAY GUN 16x1,5mm CONN.
6381052	HP2 HOSE 3/8" MT.10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP

ACCESSORIES KIT	
TRK4825P	REPAIR KIT GASKET PUMP
6836295I	S.STEEL SUCTION HOSE Ø25 F36x2 90° M28x1,5 120mm
6836295AK	FM21906 S. STEEL SUCTION FILTER RACC F28x1,5mm 30M
RAP4860	R7 RETURNED HOSE Ø1/4" MT1.8 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP4825A	APOLLO 48 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKP4825B	APOLLO 48 Pneumatic airless piston pump on bracket - Pressure regulator - Stainless steel inline filter



CODE	DESCRIPTION
TKP4825D	APOLLO 48 Pneumatic airless piston pump C/ Stainless steel inline filter



APOLLO
66

Pneumatic airless piston pump for high pressure professional paint spraying, suitable for treating paint and anti-corrosion with high viscosity products.

CODE	DESCRIPTION
TKP6618C	APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

		APOLLO 66
Ratio		66:1
Pump capacity per cycle	cm³	100
Stroke	mm	100
Max. Delivery free flow	ltr/min	15
Number of strokes per liter	Bar (PSI)	10
Max. Working outlet pressure	Bar (PSI)	528 (7657)
Max. Air inlet pressure	Bar (PSI)	8 (116)
Weight	kg.	64
Air consumption	ltr/min	600 -2650
Packing type		Fixed
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm
Packing material		PTFE-PE-LEATHER

APPLICATION

Suitable for treating paint and anti-corrosion with high viscosity products. It can be used in the naval, civil and industrial construction sectors and heavy carpentry, with bicomponent products, paint, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins. All the components in the fluid section are in stainless steel and tungsten carbide, to always guarantee the best quality.



ACCESSORIES KIT	
RST22	HP RST2 SPRAY GUN 16x1,5mm CONN.
6381052	HP HOSE 3/8" MT.10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP

ACCESSORIES KIT	
TRK6618P	REPAIR KIT GASKET PUMP
6836295I	6836295I S.STEEL HOSE Ø25 F36x2mm 90° M28x1,5mm 1200mm
6836295AK	FM21906 S. STEEL SUCTION FILTER F28x1,5 CONN. 30M
	RAP4860 R7 RETURNED HOSE Ø1/4" MT1.8 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TKP6618A	APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - Complete suction system



CODE	DESCRIPTION
TKP6618B	APOLLO 66 Pneumatic airless piston pump on bracket - Pressure regulator - Stainless steel inline filter



CODE	DESCRIPTION
TKP6618D	APOLLO 66 Pneumatic airless piston pump C/ Stainless steel inline filter



B24

Pneumatic double diaphragm pump suitable for low-pressure air spraying with paint atomization air or low-medium viscosity fluid transfer. Available in the plastic variant **BOXER**.

CODE	DESCRIPTION
212404	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator - LP hose 7,5m - Spray gun - Complete suction system

B24		
Motor		Pneumatic
Compression ratio		1:1
Max. Delivery free flow	ltr/min	24
Max. Working inlet pressure	Bar (PSI)	8 (116)
Max. Working outlet pressure	Bar (PSI)	8 (116)
Weight	kg.	11
Air consumption	ltr/min	200 - 500
Material inlet fitting size		M 1/2"
Material outlet fitting size		M 3/8"

APPLICATION

It can be used with enamels, lacquers, base coats and varnishes, in the wood and metal sector.



ACCESSORIES KIT	
10710XX	S 710 SPRAY GUN SSP
6668750	LP TWIN HOSE 6x8 mt. 7,5 RACC 1/4"
040119K	NYLON KIT DIAPHRAGM B24 / BOXER
040224K	RUBBER KIT DIAPHRAGM + PTFE B24 / BOXER

ACCESSORIES KIT	
520003	6L GRAVITY TANK "L" ADAPTER
	690012 S. STEEL SUCTION SYSTEM Ø13 F1/2" M15x1" 750mm
690012K	FM60005 SUCTION HOUSING KIT F15x1"
	35068 RILSAN HOSE 6x8 1MT



CODE	DESCRIPTION
212405	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator - LP hose 7,5m - Spray gun - Gravity tank with adapter



CODE	DESCRIPTION
212403	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator



CODE	DESCRIPTION
212402	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter



CODE	DESCRIPTION
212400	B24 Pneumatic double diaphragm transfer pump C/ Pressure regulator
212401	B24 Bare pneumatic double diaphragm transfer pump



CODE	DESCRIPTION
TK13000	BOXER Pneumatic double diaphragm transfer pump C/ Pressure regulator
TK13001	BOXER Bare pneumatic double diaphragm transfer pump



ARES
4200

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products. Available with vertical or horizontal engine.

CODE	DESCRIPTION
TKG42C	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank

ARES 4200		
Motor Volt		230 Volt 50 Hz
Variant		380 Volt 110 Volt
Power		0,74 Kw
Max. Delivery free flow	ltr/min	4
Max. tip	1 Gun	0,021
	2 Guns	0,013
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	200 (2900)
Max. length hose	mt	60
Max. elevation hose	mt	60
Weight	Kg	26
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm

ACCESSORIES KIT	
RST12	HP RST12 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
614755	HP HOSE 1/4" MT 7,5 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
TR4103	COMPLETE ARES 4200 DIAPHRAGM
69036212AK	69036212I S. STEEL SUCTION HOSE Ø19 F36x2 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	610202I S. STEEL RETURNED HOSE F20x2mm MT 0,75

APPLICATION

It can be used with enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints.
The Tsunami/Ares pumps are suitable for low viscosity water-based paints and mural injection resins.



CODE	DESCRIPTION
TKG42E	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system



CODE	DESCRIPTION
TKG42B	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - Gravity tank



CODE	DESCRIPTION
TKG42F	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - Complete suction system



CODE	DESCRIPTION
TKG42D	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and vertical C/ Trolley - Manometer - Gravity tank



CODE	DESCRIPTION
TKG42A	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and vertical C/ Trolley - Manometer - Complete suction system



NEW



ARES 4200

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products. Portable. Practical and handy.

CODE	DESCRIPTION
TKG42G	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Hand trolley - Manometer - HP hose 7,5m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank

ARES 4200		
Motor Volt		230 Volt 50 Hz
Variant		380 Volt 110 Volt
Power		0,74 Kw
Max. Delivery free flow	ltr/min	4
Max. tip	1 Gun	0,021
	2 Guns	0,013
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	200 (2900)
Max. length hose	mt	60
Max. elevation hose	mt	60
Weight	Kg	26
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm

APPLICATION

It can be used with enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints. The Tsunami/Ares pumps are suitable for low viscosity water-based paints and mural injection resins.

ACCESSORIES KIT	
RST12	HP RST12 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
614755	HP HOSE 1/4" MT 7,5 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
TR4103	COMPLETE ARES 4200 DIAPHRAGM
69036212AK	69036212I S. STEEL SUCTION HOSE Ø19 F36x2 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	610202I S. STEEL RETURNED HOSE F20x2mm MT 0,75



CODE	DESCRIPTION
TKG42H	ARES 4200 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Hand trolley - Manometer - Gravity tank





TSUNAMI 65

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces.

CODE	DESCRIPTION
TKU65E	TSUNAMI 65 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

TSUNAMI 65		
Motor Volt		230 Volt 50 Hz
Variant		380 Volt 110 Volt
Power		1,49 Kw
Max. Delivery free flow	ltr/min	7,5
Max. tip	1 Gun	0,037
	2 Guns	0,017
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	220 (3190)
Max. length hose	mt	100
Max. elevation hose	mt	100
Weight	Kg	54
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm

ACCESSORIES KIT	
RST22	HP RST12 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
614755	HP HOSE 1/4" MT 7,5 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61350	WHITE 35 L GRAVITY TANK

ACCESSORIES KIT	
FM61340	ADAPTER M 2" F36x2mm + FILTER + GASKET
TR10103	COMPLETE TSUNAMI 65 DIAPHRAGM
683629I	S. STEEL SUCTION SYSTEM Ø25 F36x2 90° M28x1,5 750mm
FM2903	S. STEEL SUCTION FILTER F28x1,5mm M 30
610202I	S. STEEL RETURNED HOSE F 20x2mm M 0.75

APPLICATION

Suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products, enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints and mural injection resins. The Tsunami/Ares pumps are suitable for low viscosity water-based paints and mural injection resins.



CODE	DESCRIPTION
TKU65F	TSUNAMI 65 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - 35L gravity tank



CODE	DESCRIPTION
TKU65A	TSUNAMI 65 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - Complete suction system



CODE	DESCRIPTION
TKU65D	TSUNAMI 65 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - 35L gravity tank



TSUNAMI 11

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces.

CODE	DESCRIPTION
TKU11E	TSUNAMI 11 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

TSUNAMI 11		
Motor Volt		230 Volt 50 Hz
Variant		380 Volt 110 Volt
Power		2,23 Kw
Max. Delivery free flow	ltr/min	9,5
Max. tip	1 Gun	0,043
	2 Guns	0,019
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	220 (3190)
Max. length hose	mt	100
Max. elevation hose	mt	100
Weight	Kg	54
Material inlet fitting size		M 36x2 mm
Material outlet fitting size		M 16x1,5 mm

ACCESSORIES KIT	
RST22	HP RST12 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
614755	HP HOSE 1/4" MT 7,5 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61350	WHITE 35 L GRAVITY TANK

APPLICATION

Suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products, enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints and mural injection resins.

The Tsunami/Ares pumps are suitable for low viscosity water-based paints and mural injection resins.

ACCESSORIES KIT	
FM61340	ADAPTER M 2" F36x2mm + FILTER + GASKET
TR10603	COMPLETE TSUNAMI 11 DIAPHRAGM
683629I	S. STEEL SUCTION HOSE Ø25 F36x2 90° M28x1,5 750mm
FM2903	S. STEEL SUCTION FILTER F28x1,5mm M 30
610202I	S. STEEL RETURNED HOSE F 20x2mm M 0.75



CODE	DESCRIPTION
TKU11F	TSUNAMI 11 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - 35L Gravity tank



CODE	DESCRIPTION
TKU11A	TSUNAMI 11 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - Complete suction system



CODE	DESCRIPTION
TKU11D	TSUNAMI 11 Electric airless diaphragm pump volt 230/Hz50 single phase and horizontal C/ Trolley - Manometer - 35L Gravity tank



Peristaltic pump for low pressure paint spraying suitable in the construction sector for medium-large surfaces. Suitable for the professional painting of interior and exterior plastering, renovations, waterproofing and industrial buildings.

CODE	DESCRIPTION
TI7600	MISTRAL Volumetric rotative peristaltic pump volt 230/Hz50 - C/ Trolley - 35L Gravity tank - Remote control - Bear lance - On/Off remote control - 5 Stainless steel sets nozzles - Twin hose 10m

		MISTRAL
Motor Volt		230 Volt 60 Hz
Power		0,55 Kw
Max. Delivery free flow	ltr/min	8,5
Max. Working outlet pressure	Bar (PSI)	15 (218)
Weight	Kg	55
Air consumption		300-600

APPLICATION

Mistral can only be used with a gun equipped with an electronic remote control. It's suitable for all liquid and pasty products, because it is based on a unique volumetric rotating system. It is able to spray paint on all products with a grain size of up to 2.5mm including plasters, decorative laminates, anti-skid and bitumen materials, silicate resins, thermal insulators, insulating pastes, porous cement coatings, putties, artificial resins, fillers, primers, quartz paints, bituminous, fireproof and soundproofing coatings.

ACCESSORIES KIT	
TR78621	STAINLESS STEEL Ø10,5 NOZZLE FOR LANCE
TR78622	STAINLESS STEEL Ø8,5 NOZZLE FOR LANCE
TR78623	STAINLESS STEEL Ø6,5 NOZZLE FOR LANCE

ACCESSORIES KIT	
TR78624	STAINLESS STEEL LANCE Ø4,5
TR78625	STAINLESS STEEL FLAT SHAPE NOZZLE
TT78600	BEAR LANCE



Line marking diaphragm pump suitable to light duties line marking operations for parking lots and touch up jobs spraying medium and low viscosity road paints. GEA 4200 was designed to trace lines in road works, parking lines, industrial signs, playgrounds and bicycle lanes.

CODE	DESCRIPTION
TKLA	GEA 4200 Line marking airless diaphragm pump - Gas engine C/ Manometer - Hose 10m - RST1 spray gun - Tip guard - Reversible tip - Complete suction system

		GEA 4200
Motor Volt		HONDA
Power		3,5 Hp
Max. Delivery free flow	ltr/min	4
Max. tip	1 Gun	0,021
	2 Guns	0,013
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	200 (2900)
Max. length hose	mt	60
Max. elevation hose	mt	60

APPLICATION

The GEA pump has an autonomous gas engine which makes it light and easy to handle. Furthermore, thanks to its quick gun coupling system, it is possible to remove the gun from the central trolley and use it individually for further works. Thanks to the directional front wheel with 5 different positions, it is possible to trace straight lines or lines with two different radius measurements.



ACCESSORIES KIT	
RST12	HP RST2 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FMLMXXX	FMLMXXX REVERSIBLE TIP

ACCESSORIES KIT	
TR4103	COMPLETE GEA 4200 DIAPHRAGM
69036212AK	69036212I.S. STEEL SUCTION HOSE Ø19 F36x2mm M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
6102021	S. STEEL RETURNED HOSE F20x2mm MT0.75



GEA 11000

Line marking diaphragm pump suitable to light duties line marking operations for parking lots and touch up jobs spraying medium and low viscosity road paints. GEA 11000 was designed to trace lines in road works, parking lines, industrial signs, playgrounds and bicycle lanes.

CODE	DESCRIPTION
TKLC	GEA 11000 Line marking airless diaphragm pump with gas engine C/ Manometer - Hose 10m - RST2 spray gun - Tip guard - Reversible tip - Complete suction system

GEA 11000		
Motor Volt		HONDA
Power		11,7 Hp
Max. Delivery free flow	ltr/min	9,5
Max. tip	1 Gun	0,043
	2 Guns	0,019
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	220 (3190)
Max. lenght hose	mt	100
Max. elevation hose	mt	100

APPLICATION

The GEA pump has an autonomous gas engine which makes it light and easy to handle. Furthermore, thanks to its quick gun coupling system, it is possible to remove the gun from the central trolley and use it individually for further works. Thanks to the directional front wheel with 5 different positions, it is possible to trace straight lines or lines with two different radius measurements.



ACCESSORIES KIT	
RST22	HP RST2 SPRAY GUN M16x1,5mm CONN.
614105	HP HOSE 1/4" MT 10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FMLMXXX	FMLMXXX REVERSIBLE TIP

ACCESSORIES KIT	
TR10603	COMPLETE GEA 11000 DIAPHRAGM
683629I	S. STEEL SUCTION HOSE Ø25 F36x2 90° M28x1,5mm 750mm
FM2903	S. STEEL SUCTION FILTER F28x1,5 30M
610202I	S. STEEL RETURNED HOSE F 20x2mm MT 0.75





MIURA
21000

Hydraulic piston pump for airless high-pressure professional paint spraying suitable for treating paint and anti-corrosion with high viscosity products. Available with gas or electric engine.

CODE	DESCRIPTION
TKH21D	MIURA 21000 Hydraulic airless piston pump Volt 230/Hz50 single phase C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system

APPLICATION They can be used in the naval, civil and industrial construction sectors and heavy carpentry with paints, anti-corrosives, intumescent coatings, protective coatings and encapsulants, putties, fillers, injection resins and ready-mix stucco.

MIURA 21000		
Motor Volt	230 Volt 50 Hz	
Variante	380 Volt 50 Volt	
Power	2,23 Kw	
Max. Delivery free flow	ltr/min	6,5
Stroke	mm	80
Max. tip	1 Gun	0,035
	2 Guns	0,017
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	240 (3480)
Max. length hose	mt	100
Max. elevation hose	mt	100
Packing material	Kg	PTFE
Material outlet fitting size	M 16x1,5 mm	

ACCESSORIES KIT	
RST22	HP RST2 SPRAY GUN 16x1,5mm CONN.
6381052	HP2 HOSE 3/8" MT.10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP

MIURA 21000G		
Motor	HONDA	
Power	8,4 Hp	
Max. Delivery free flow	ltr/min	6,8
Stroke	mm	
Max. tip	1 Gun	0,037
	2 Guns	0,017
	3 Guns	---
Max. Working outlet pressure	Bar (PSI)	280 (4061)
Max. length hose	mt	100
Max. elevation hose	mt	100
Packing material	PTFE	
Material outlet fitting size	M 16x1,5 mm	

ACCESSORIES KIT	
TR21603	UPPER AND LOWER PACKING SET
6803625I	S.STEEL SUCTION HOSE Ø25 F36x2mm M28x1,5mm 1200mm
FM21906	S.STEEL SUCTION FILTER F28x1,5 30M CONN.
6102025I	S.STEEL RETURNED HOSE F 20x2mm 1200mm



CODE	DESCRIPTION
TKH21E	MIURA 21000 Hydraulic airless piston pump volt 230/Hz50 single phase C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Direct suction



CODE	DESCRIPTION
TKH21A	MIURA 21000 Hydraulic airless piston pump volt 230/Hz50 single phase C/Trolley - Inline filter - Manometer - Direct suction



CODE	DESCRIPTION
TKH21F	MIURA 21000 Hydraulic airless piston pump with gas engine C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system



CODE	DESCRIPTION
TKH21G	MIURA 21000 Hydraulic airless piston pump with gas engine C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Direct suction



CODE	DESCRIPTION
TKH21C	MIURA 21000 Hydraulic airless piston pump with gas engine C/Trolley - Inline filter - Manometer - Direct suction



CODE	DESCRIPTION
TKH44D	MIURA 44000 Hydraulic airless piston pump Volt 230/Hz50 single phase C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system





APPLICATION It can be used with paints, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins.

	MIURA 44000
Motore Volt	230V
Power	2,23 Kw
Max. Delivery free flow	litr/min 10,5
Stroke	mm 100
Max. tip	1 Gun 0,037 2 Guns 0,017 3 Guns ---
Max. Working outlet pressure	Bar (PSI) 240 (3480)
Max. length hose	mt 150
Max. elevation hose	mt 150
Packing material	PTFE
Material outlet fitting size	M 16x1,5 mm

ACCESSORIES KIT	
RST22	HP RST2 SPRAY GUN 16x1,5mm CONN.
6381052	HP2 HOSE 3/8" MT.10 M16x1,5mm CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP

	MIURA 44000	MIURA 44000G
Motore Volt	380V	HONDA
Power	4 Kw	11,7 Hp
Max. Delivery free flow	litr/min 14,2	14,2
Stroke	mm 100	100
Max. tip	1 Gun 0,063 2 Guns 0,036 3 Guns 0,023	0,063 0,036 0,023
Max. Working outlet pressure	Bar (PSI) 280 (4061)	280 (4061)
Max. length hose	mt 150	150
Max. elevation hose	mt 150	150
Packing material	PTFE	PTFE
Material outlet fitting size	M 16x1,5 mm	M 16x1,5 mm

ACCESSORIES KIT	
TR44806	UPPER AND LOWER PACKING SET
6803625I	S. STEEL SUCTION HOSE Ø25 F36x2mm M28x1,5 1200mm
683625AK	FM21906 S. STEEL SUCTION FILTER F28x1,5mm 30M CONN.
6102025I	S. STEEL RETURNED HOSE F 20x2mm 1200mm





miura
21000 mix

Two component hydraulic airless piston pump, suitable for painting and anti-corrosion treatment with high viscosity products. Available in two variants: MIX 9 and MIX 18.

MIX 9

CODE	DESCRIPTION
TK21400	MIURA 21000 MIX 9 Two component hydraulic airless piston pump Volt 230/50 HZ single phase C/ Trolley - 2 Inline filters - 2 Manometers - 2 Complete suction systems

	MIURA 21000 MIX 9
Motor Volt	230V 50 Hz
Power	2,23 Kw
Mixing ratio	1:1
Stroke mm	80
Max. Delivery free flow Bar (PSI)	9
Max. Working outlet pressure ltr/min	220 (3190)
Material outlet fitting size	M 16x1,5 mm

APPLICATION

It can be used with bicomponent products, paints, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins.

ACCESSORIES KIT	
RST21	HP RST2 SPRAY GUN 1/4" CONN.
614104	HP HOSE 1/4" MT10 1/4" CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
FM610062	"U" OBLIQUE ADAPTER M36x2mm X F36x2mm
TRK4010P	REPAIR KIT GASKET PUMP
69034912AK	69034912I S.STEEL SUCTION SYSTEM Ø19 F36x2mm 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	RAP3040 R7 RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TK21401	MIURA 21000 MIX 9 Two component hydraulic airless piston pum with gas engine C/ Trolley - 2 Inline filters - 2 Manometers - 2 Complete suction systems



miura
21000 mix

Two component hydraulic airless piston pump, suitable for painting and anti-corrosion treatment with high viscosity products. Available in two variants: MIX 9 and MIX 18.

MIX 18

CODE	DESCRIPTION
TK21450	MIURA 21000 MIX 18 Two component hydraulic airless piston pump Volt 230/50 HZ single phase C/ Trolley - 2 Inline filters - 2 Manometers - 2 Complete suction systems

	MIURA 21000 MIX 18
Motor Volt	230V 50 Hz
Power	2,23 Kw
Mixing ratio	1:1
Stroke mm	80
Max. Delivery free flow Bar (PSI)	18
Max. Working outlet pressure ltr/min	120 (1740)
Material outlet fitting size	M 16x1,5 mm

APPLICATION

It can be used with bicomponent products, paints, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins.

ACCESSORIES KIT	
RST21	HP RST2 SPRAY GUN 1/4" CONN.
614104	HP HOSE 1/4" MT 10 1/4" CONN.
201203	TIP GUARD FOR REVERSIBLE TIPS
FM6XXX	FM6XXX REVERSIBLE TIP
FM61000	WHITE 6L GRAVITY TANK

ACCESSORIES KIT	
FM610062	"U" OBLIQUE ADAPTER M36x2 X F36x2mm
TRK4010P	REPAIR KIT GASKET PUMP
69034912AK	69034912I S.STEEL SUCTION SYSTEM Ø19 F36x2mm 90° M1/2" 750mm
	FM60004 SUCTION HOUSING KIT F1/2"
	RAP3040 R7 RETURNED HOSE Ø1/4" MT1.5 F1/4" CONN. ONE SIDE



CODE	DESCRIPTION
TK21451	MIURA 21000 MIX 18 Two component hydraulic airless piston pum with gas engine C/ Trolley - 2 Inline filters - 2 Manometers - 2 Complete suction systems